



FLOOR CARE

Distance[®]

ultra high speed floor finish

TECHNICAL DATA SHEET

Packaging	Code
4 x 4 L	1497278002
20 L	1497334001
210 L	1497390001

Description:

DISTANCE is a crystal clear, high gloss, thermacrylic finish with superior dirt and black mark resistance. This versatile floor finish is ideal for both hard and resilient floors and respond well to varying spray-buff or spray burnishing maintenance schedules.

Use Direction:

- Completely remove old finish and rinse the floor thoroughly. Allow to dry.
- Apply one or two coats of compatible floor sealer and let dry.
- Apply two or three coats of U.H.S. floor finish. Allow 30 minutes drying time between coats.
- Burnishing when dry is optional.

WEEKLY MAINTENANCE:

- Using a burnisher, polish the floor to remove scratches and scuff marks. In high traffic areas, apply a coat of U.H.S. floor finish.
- The use of a compatible shine restorer keeps floors clean and shiny.

DAILY MAINTENANCE:

- Dust mop using non treated dry mop. Wash floor with neutral detergent in cold water.

AUTHORIZED BY CANADIAN FOOD INSPECTION AGENCY FOR USE IN REGISTERED ESTABLISHMENTS.

Security:

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	0
0 =	Insignificant
1 =	Slight
2 =	Moderate
3 =	High
4 =	Very High

Note:

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.

Technical Specifications:

Appearance	Opaque liquid
Colour	White
Odour	Light acrylic
Specific Gravity	1.030 – 1.040
pH	8.1 – 8.4
Solids	19.0 – 20.0%