



SAFETY DATA SHEET WEBBGRIP RAPIDE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME WEBBGRIP RAPIDE
PRODUCT NO. 80018
APPLICATION Adhesive
SUPPLIER Tremco illbruck Production Limited
 Coupland Road
 Hindley Green
 Wigan WN2 4HT
 England
 Tel : +44 (0)1942 258011
 Fax : +44 (0)1942 521923
 email : msds@tremco-illbruck.co.uk
CONTACT PERSON R P Brisbourne
EMERGENCY TELEPHONE (+44) 1942 258011

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
DSP 60/95 S (LOW B.P. MODIFIED NAPHTHA SOLVENT-REFINED LIGHT)			10 - 20%	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
TOLUENE	203-625-9	108-88-3	< 10%	F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Highly flammable.

Vapours may cause drowsiness and dizziness.

Irritating to skin.

Possible risk of harm to the unborn child.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Rep 3;R63. Xi;R38. F;R11. R52/53, R67.

4 FIRST-AID MEASURES

INHALATION

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

INGESTION

Do not induce vomiting. Rinse mouth thoroughly. Get medical attention.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention immediately

5 FIRE-FIGHTING MEASURES

WEBBGRIP RAPIDE

EXTINGUISHING MEDIA

Extinguish with carbon dioxide or dry powder.

SPECIFIC HAZARDS

In case of fire, toxic gases may be formed.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. Do not smoke, use naked flames or other sources of ignition.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Collect with absorbent, non-combustible material into suitable containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Provide good ventilation. Eliminate all sources of ignition.

STORAGE PRECAUTIONS

Store in tightly closed original containers in a cool, dry, well-ventilated place. Keep away from heat, sparks and open flame.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
DSP 60/95 S (LOW B.P. MODIFIED NAPHTHA SOLVENT-REFINED LIGHT)	SUP	315 ppm	1200 mg/m3		
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	150 ppm(Sk)	574 mg/m3(Sk)

INGREDIENT COMMENTS

SUP = Supplier's recommendation. WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Paste
COLOUR	Beige.
ODOUR	Aromatic.
SOLUBILITY	Insoluble in water

WEBBGRIP RAPIDE

BOILING POINT (°C) 80 - 120°C RELATIVE DENSITY 1.18
 FLASH POINT (°C) -26°C

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Contains Toluene which is suspected of causing harm to the unborn child.

INHALATION

May cause irritation to the respiratory system. Vapours may cause drowsiness and dizziness.

SKIN CONTACT

Irritating to skin.

EYE CONTACT

May cause irritation.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Contains some solvents which are harmful aquatic organisms and may persist in the aquatic environment.

DEGRADABILITY

The product is not biodegradable.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

WASTE CLASS

Hazard Classification : H3A, H4, H5, H10, H14 EWC Code: 08 04 09

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME	ADHESIVES		
UN NO. ROAD	1133	ADR CLASS NO.	3
ADR PACK GROUP	III	HAZARD NO. (ADR)	33 Highly flammable liquid (flash-point below 23°C).
ADR LABEL NO.	3	UN NO. SEA	1133
IMDG CLASS	3	IMDG PACK GR.	III
UN NO. AIR	1133	AIR CLASS	3
AIR PACK GR.	III		

WEBBGRIP RAPIDE

15 REGULATORY INFORMATION

LABELLING



Harmful



Highly Flammable

CONTAINS

TOLUENE

RISK PHRASES

R11	Highly flammable.
R38	Irritating to skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S24	Avoid contact with skin.
S36/37	Wear suitable protective clothing and gloves.
S51	Use only in well-ventilated areas.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P11	Restricted to professional users.

UK REGULATORY REFERENCES

Chemicals (Hazard Information and Packaging for Supply) (Amendment) Regulations 2005 (CHIP 3.1)

EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EC

GUIDANCE NOTES

Workplace Exposure Limits EH40. Hazardous Waste Regulations (2005)

16 OTHER INFORMATION

REVISION DATE 24th November 2006

REV. NO./REPL. SDS GENERATED 7th June 2005

RISK PHRASES IN FULL

R11	Highly flammable.
R38	Irritating to skin.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.