

# suregrip

## Safety Tape Range

Instant slip resistance for steps, ramps, paths, floors, vehicles etc.

T: +44 (0) 1707 800060  
F: +44 (0) 1707 657282  
E: [info@versatileflooring.co.uk](mailto:info@versatileflooring.co.uk)  
[www.versatileflooring.co.uk](http://www.versatileflooring.co.uk)



Long lasting, self-adhesive and slip resistant tape available in a wide variety of colours, widths and lengths from stock for quick, simple and effective anti-slip solutions.

The Suregrip range of anti-slip conformable, self-adhesive tapes will help to improve safety on profiled metal, concrete, stone, painted and wooden surfaces. Quick and simple to install, the SureGrip safety tape range is supplied with a comprehensive range of primers and edge sealers.

For areas subject to heavier wear or high pedestrian or vehicle movements please ask about the suregrip range of GRP stair treads, edge covers and decking.

### Key Benefits

- **Self adhesive - easy to apply.**
- **Improves safety quickly and simply.**
- **Resin-bonded grit improves durability.**
- **Highly visible, identifies the step edge.**
- **Ideal for concrete, wood, terrazzo, metal, and painted surfaces.**
- **Ideal for stairs, steps, ramps and entrance halls.**
- **Water resistant pressure sensitive adhesive backing**
- **Helps achieve the requirements of Disabled Discrimination Act and Part M 2004 building regulations .**
- **Suitable for internal and external applications.**



For more information on our extensive range of interlocking floor tiles, anti-slip safety products, line marking tapes and ergonomic matting please visit our web site at

[www.versatileflooring.co.uk](http://www.versatileflooring.co.uk)

## Storage

Store in warm, dry conditions prior to use.

## Surface Preparation

Apply to clean, smooth, dry surfaces such as painted or varnished wood, concrete, metal, tiles and terrazzo. Apply direct to smooth, hard concrete; dusty concrete will require a primer.

## Priming

Smooth, non porous, dust free surfaces do not require priming. To improve adhesion on weak, dusty surfaces, apply a coat of Safety Tape Primer.

## Application

Avoid application at temperatures below 10°C. Low temperatures can reduce adhesion. On steps and nosings, apply the product approximately 10mm in from the edge to prevent premature wear and edge curl. Peel back the backing strip approximately 50mm to reveal the adhesive layer. Avoid removing too much of the backing strip, but slowly keep peeling it back whilst firming the product into place. Firming down by hand or foot pressure is generally sufficient. A rubber mallet is recommended for firming Suregrip Safety Tape Conformable Treads (the flexible, aluminium backed products) into place. Avoid stretching the tapes and treads during application.

## Adhesion

Although the product can be walked on virtually straight away, the adhesive can take 24 hours to set fully. Immediately after placing the item onto the substrate, it can be peeled off reasonably easily. Please allow the adhesive to set if using in heavily trafficked or hazardous areas.

## Suregrip Safety Tape Edge Sealer

Safety Tape Edge Sealer is recommended in wet or heavy wear areas. This clear sealer is squeezed directly from a tube around the edges of the tread or tape. It protects the edges and helps reduce water ingress. Apply Safety Tape Edge Sealer after the tape or tread has been firmed into place.

## Suregrip Safety Tape Primer

### Instructions

Safety Tape Primer will improve adhesion on dusty, friable surfaces. Not required on smooth, non porous surfaces such as paint, varnish, tiles etc. Do not apply to metal.

## Application

After stirring, apply one coat of primer by brush at a coverage rate of approximately 2 - 3 sq. metre per 500ml. Allow to dry (the product is milky when applied, then turns clear upon drying). Dries in 1 hour at 10 - 15°C. Only apply the primer to the area that will be covered by the tape or tread. Uncovered primer could remain tacky and attract dirt. Apply the Suregrip Safety Tape according to the instructions.

## Limitations

Do not apply in wet conditions or at temperatures below 10°C.

## Cleaning of Equipment

Brushes should be washed in water. All products are available direct from The Versatile Flooring Co. Ltd.

Product Range & Prices			
DESCRIPTION	50MM	75mm	100mm
Anti-slip tape (18m roll) Available in black, yellow, transparent or black/yellow hazard stripes	£39.95	£49.95	£59.95
Anti-slip Treads 610 x 150mm Available in black, yellow or black/yellow hazard stripes	£7.50 each / £49.50 pack of 10 / £199.50 pack of 50		
Anti-slip photo luminescent tape	£65.00 per 18m x 50mm wide roll		
55mm DDA Anti-slip tape (18m roll) covers the going and riser of the step	£45.00 or £219.50 for a pack of 6 rolls		
Conformable Anti-slip tape for uneven surfaces. Black or yellow	£69.50 per 18m x 50mm wide roll		
Barefoot grade anti-slip tape for shower / changing rooms	£39.95 per 18m x 50mm roll or £199.50 per pack of 6 rolls		
Anti-slip walkway / ramp tape in black only or black/yellow hazard stripes	Black - £199.50 per 9.1m x 610mm roll or Black/Yellow - £149.50 per 9.1m x 508mm roll		
Anti-slip Tape Edge Sealer 2 tubes per 18m roll	£7.99 per 140ml		
Anti-slip Tape Primer 1 unit sufficient for 2 rolls of 18m x 50mm	£9.99 per 1l unit		

## Terms and Conditions of Sale

All products are sold subject to the Company's Standard Conditions of Sale. The Company and its representatives are often asked to comment on potential uses of The Versatile Flooring Co. Ltd. products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by The Versatile Flooring Co. Ltd.

 **The Versatile Flooring Company**  
1 Devonshire Business Centre  
Cranborne Industrial Estate  
Potters Bar Hertfordshire EN6 3JR  
**T: + 44 (0) 01707 800060**  
**F + 44 (0) 1707 657282**  
www.versatileflooring.co.uk  
info@versatileflooring.co.uk

