



BRE Green Guide 2008 rating & VOC Data

EcoTile Interlocking Floor Tiles (5mm, 6mm, 7mm & 10mm including ESD/Anti-static)

Building type >	Industrial / Commercial / Retail
Category >	Floor Finishes
Element type >	Resilient Floor Finishes
Element	Durability: Homogeneous polyvinyl chloride floor coverings (EN 649). FCSS 33, 34.
Element Number	821570038
Summary Rating	A+
Climate Change	A=
Water Extraction	A+
Mineral Resource Extraction	A+
Stratospheric Ozone Depletion	A
Human Toxicity	A+
Ecotoxicity to Freshwater	A+
Nuclear Waste (higher level)	A
Ecotoxicity to Land	A+
Waste Disposal	A+
Fossil Fuel Depletion	A+
Eutrophication	A+
Photochemical Ozone Creation	A
Acidification	A+
Kg of CO ₂ eq. (60 years)	43.0
E1 level as per BS EN 717-1: Formaldehyde – Concentration / $\mu\text{g}/\text{m}^3 < 3$	
Performance requirements - Option 1 - Formaldehyde E1 Class	
Compliant performance standard: BS EN 14041:2006 Resilient, textile and laminate floor coverings - Essential characteristics	
Compliant testing standards: BS EN 717-1:2004 Wood-based panels – Determination of formaldehyde release - Part 1: Formaldehyde emission by the chamber method	