



	Studded (Raised Disc)
Dimensions:	505mm x 505mm
Thickness:	4.5mm +/- 0.3mm
Weight:	5.3kgs/m ²
Guarantee:	5 Years
Anticipated Service Life:	10 Years +
Material:	PVC
Joint:	Dovetail

		Smooth
Slip Resistance:	EN 14041:2004 DIN 51130:2004	Pass R10
Fire Performance:	BS 476: Part 7 DIN 13501: 2007	Class 1 Spread of Flame Bfl-S1 Does not support combustion
Stain Resistance:	EN 423	Good
Abrasion Wear Resistance:	EN 13845 EN 649	50K Cycles Group T
Mechanical Resistance:	DIN 53516	17N/mm ²
Resistance to Hot Objects/Solder:		Good
Thickness of Wear Layer:	EN 429	4.5 mm
Hardness:	ISO 868	89-92 Shore A
Impact Resistance:	EN 13329-549	549kg/cm ²
Noise Reduction:	EN 140-8	>46db
Thermal Insulation:		1.26 m ² K/W
Determination of Length, Squareness & Straightness:	BS EN 428:1993	<0.13% / 0.5mm max.
Chemical Resistance:	EN 13529	Good resistance to most commonly used chemicals. Common acid oils & gas oil - No deterioration / Not Resistant to prolonged contact
Colour Fastness:	EN 50105-BO21	5



Manufactured by:
Ecotile Flooring Ltd
Unit 15 North Luton Industrial Estate
Sedgwick Road, Luton, LU4 9DT
Tel: +44 (0) 1582 788 232
Fax: +44 (0) 2089 299 150
www.ecotileflooring.com



26O2019 - QMS & 27O2019 - EMS