



TECHNICAL DATA SHEET

	Stone Effect	Wood Effect
Dimensions:	61cm x 61cm	66cm x 33cm
Thickness:	8.2mm	8.2mm
Weight:	11 kgs/m ²	11 kgs/m ²
Slip Resistance:	Pass R10	Pass R10
Water Tight:	With Sealant	With Sealant
Tile Material:	Fibreglass Reinforced PVC	Fibreglass Reinforced PVC
Wear Resistance:	Class T	Class T
Fire Performance:	Class 1 Spread of Flame Bfl-S1 Does not support combustion	Class 1 Spread of Flame Bfl-S1 Does not support combustion
Surface Treatment:	Protectonite (PUR)	Protectonite (PUR)
Furniture Push Test:	No Cracks, No Damage	No Cracks, No Damage
Thickness of Vinyl Wear Layer:	0.55mm	0.55mm
Noise Reduction:	16db	16db
Anti-static Properties	<2kv	<2kv
Determination of Length, Squareness & Straightness:	<0.15	<0.15
Vehicle Use	Hand Pallet Truck - 2.5 tonnes Electric Pallet Truck with PU wheels - 3.0 tonnes Forklift with 4 x Solid Rubber Wheels - 5.0 tonnes	

Trusted, Accredited Supplier

ecovadis



Take The Next Step Towards *infinity*

Head Office, Factory & Showroom
Unit 15 North Luton Industrial Estate,
Sedgwick Road, Luton, LU4 9DT

01582 788 232
ecotileflooring.com
hello@ecotileflooring.com